
Uncovering the Quality and Quantity Issues of Wisconsin's Buried Treasure




Jim Krohelski - U.S. Geological Survey George Kraft – Central Wisconsin Groundwater Center Ken Bradbury - Wisconsin Geological and Natural History Survey









All water on earth is part of the water cycle



Groundwater moves from recharge areas to discharge areas



Wisconsin's Aquifers





PreCambrian aquifer:

-crystalline (granite, quartzite)

-fracture dominated flow

-generally low well yields







"Sandstone" aquifer:

- -sandstone, dolomite
- -regionally extensive
- -excellent aquifer
- -porous flow
- -most high-capacity wells
- -occurs beneath shale in east












"Dolomite" aquifer:


- -Silurian dolomite
- -fracture dominated flow
- -only present in east
- -important for municipal and domestic wells
- -occurs above Maquoketa Shale
- -extremely vulnerable if exposed










Natural



Affected By Pumping












Sources of Nitrate Loading






Whiting nitrate-N; 1963-94




Little Plover River Baseflow nitrate-N; 1966-97




Pesticides

- In the past only Atrazine and Alachlor were extensively surveyed.
- Types of pesticides in use changes rapidly.
- Frequently pesticide degradates not known or are not subject to existing methods of detection







Pesticide Detection in Wisconsin Wells

• 1995 – **14%** contain at least one pesticide residue, atrazine or alachlor (Lemasters and Baldock, 1997).

• 2000 – **38%** contain at least one pesticide. Chloroacetanlide metabolites are most prevalent. Proportion greater in agricultural districts (Rheineck, oral communication, 2001).

Emerging Contaminants - Viruses, Pharmaceuticals, Endocrine Disruptors







LaCrosse County Hydrologic Study

- Groundwater flow model indicates that some city of LaCrosse Wells withdraw water from the Mississippi River
- Selected wells tested for enteric viruses and endocrine disrupters


Pathlines—La Crosse Municipal Wells 10-year time of travel




Total Dissolved Solids Sandstone Aquifer – SE WI



Radioactivity in Sandstone Aquifer – SE WI




Arsenic




Outagamie & Winnebago Counties:

- •As >10 μg/L in 18% of residential wells
- •As > 50 μg/L in 3.5% of residential wells




Groundwater Quantity Issues


- Unacceptable drawdown due to well interference (Regional, large scale, deep aquifer).
- Undesirable depletion of baseflow and unwanted drying of wetlands (small and large scale, deep and shallow aquifers).




Lower Fox River Valley (3 ft/yr)




Southeast Wisconsin (7 ft/yr)







Lower Fox River Valley Conceptual Model




Green Bay Metropolitan Area






- Treated surface
 water is injected
 into a well and
 recovered at the
 same location
 (ASR wells)
- Injected when excess capacity is available at water treatment plant
- Storage –Seasonal and long term

Aquifer Storage and Recovery



ASR Facilities in the United States





Central Brown County Water Authority Management Alternatives


- Build independent Lake Michigan water supply system (\$132 million)
- Buy water from Green Bay Water
 Department and use ASR in 19 existing wells
- Optimize ground-water withdrawals
- Combinations

Dane County

Undesirable depletion of baseflow and unwanted drying of wetlands (large scale, deep aquifer).







▲ Groundwater discharge to surface water




Agricultural Irrigation




Undesirable depletion of baseflow and unwanted drying of wetlands (small scale, shallow aquifer).


Agricultural Irrigation 1995




Central Wisconsin Irrigated Acres



•Baseflow (1959 – 88) has not decreased



•Snowfall amount (1959 – 88) has increased



Concluding Comments

- Regional Management
- Pumping wells are optimally spaced to reduce drawdown, preserve water quality and protect highly-valued resources
- Appropriate land application rates of fertilizers and pesticides
- Collection of steamflows and groundwater levels